

## ASCENDS CarbonHawk Experiment Simulator (ACES)


PI: Michael Obland, NASA LaRC

## **Objective**

- Demonstrate measurements of column  $CO_2$  mixing ratios with a high-altitude airborne instrument architecture scalable to the ASCENDS mission requirements
  - Technologies include a high bandwidth detector and transimpedance amplifier, a multi-aperture telescope, advanced algorithms for cloud/aerosol discrimination, and high efficiency CO<sub>2</sub> and O<sub>2</sub> transmitters.
- Deploy instruments on NASA aircraft to demonstrate discrimination of surface returns from clouds and aerosols, derivation of ranging information from the continuous wave laser system, and measurements of column CO<sub>2</sub> mixing ratios



The ACES instrument inside the NASA HU-25



CO<sub>2</sub> measurements made over the Atlantic ocean

## **Accomplishments**

- Built airborne lidar measuring atmospheric column-averaged  $CO_2$  number densities and mounted in a Global Hawk-compatible environmental enclosure (2.1'x2.8'x3.7').
- Increased transmit power by 6x compared with previous instrument (to 30 watts), yielding 14x increase in power aperture product
  consistent with simulated returns over ocean and vegetated surfaces. Increased transmit power produced high signal-to-noise ratio
  measurements over challenging surfaces (e.g. ocean) with demonstrated differential optical depth measurement precisions of <0.5%.</li>
- Increased bandwidth of HgCdTe detector and electronics from 500 KHz to 4.9 MHz allowing the use of advanced laser modulation waveforms.
- Flew onboard LaRC HU-25 Falcon collecting remotely-sensed  $CO_2$  and  $O_2$  column amounts with in situ  $CO_2$  and meteorological measurements. Compiled 17.4 hours of data from multiple altitudes over land and ocean surfaces with and without intervening clouds.
  - Meets projected ASCENDS requirements for range retrievals; demonstrated retrievals of cloud and vegetation canopy structure.
  - Initial  $CO_2$  mixing ratio retrievals show reasonable agreement compared with in situ measurements (~ 1 ppm over water).

Co-Is/Partners: Ed Browell, SSAI; Jeremy Dobler, ITT Exelis; Berrien Moore, Univ. of Oklahoma; Scott Zaccheo, AER

 $TRL_{in} = 3 TRL_{out} = 5$ 

